

Mercury Outboards - Specifications - Standard Accessories - 2025.1

Information on this sheet is subject to change without notice.

	Specifications																				Standard Accessories - Single Installation																	
	Shaft Length	Counter Rotation	Tiller Handle	Remote Control	Mechanical Throttle&Shift (MTS)	Digital Throttle&Shift (DTS)	Manual Start	Electric Start	Power Tilt	Power Trim	Conventional Mid Section (CMS)	Advanced Mid Section (AMS)	Optional "Cold Fusion White" Color	Fuel System	Gear Ratio	Command Thrust Gear Case (CT)	Displacement [ccm]	Cylinder	Max. RPM at Full Throttle	Dry Weight [kg] *	Integrated Fuel Tank	Remote Fuel Tank	Fuel Quick Connect on Engine Side	Side Remote Control	Tacho Analog	Speedo Analog	Trim Gauge Analog	SC1000 Tacho SmartCraft	SC1000 Speedo SmartCraft	SC100 Trim Gauge SamrtCraft	SC100 Fuel Gauge SamrtCraft	Electro-Hydraulic Steering	Active Trim	VesselView Mobile	SeaPro Fuel Filter	Propeller		
FourStroke																																						
F2.5 M	S		x				x							Carb	2,15:1		85	1	4500-5500	18	0,95L	-	13563Q3	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax	
F3.5 M	S		x				x							Carb	2,15:1		85	1	5000-6000	18	0,95L	-		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F3.5 ML	L		x				x							Carb	2,15:1		85	1	5000-6000		0,95L	-		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F4 M	S		x				x							Carb	2,15:1		123	1	4500-5500	25	1,1L	-		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F4 ML	L		x				x							Carb	2,15:1		123	1	4500-5500		1,1L	-		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F5 M	S		x				x							Carb	2,15:1		123	1	4500-5500	25	1,1L	-		-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax	
F5 ML	L		x				x							Carb	2,15:1		123	1	4500-5500		1,1L	-		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F5 MLA Sailpower	L		x				x							Carb	2,15:1		123	1	4500-5500		1,1L	-		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F6 M	S		x				x							Carb	2,15:1		123	1	5000-6000	25	1,1L	-	8M0215251	-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax
F6 ML	L		x				x							Carb	2,15:1		123	1	5000-6000		1,1L	-		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F8 M EFI	S		x				x							EFI	2,08:1		209	2	5000-6000	40	-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F8 ML EFI	L		x				x							EFI	2,08:1		209	2	5000-6000		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F8 EH EFI	S		x				x	x						EFI	2,08:1		209	2	5000-6000		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F8 ELH EFI	L		x				x	x						EFI	2,08:1		209	2	5000-6000		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F8 EL EFI	L			x	x		x	x						EFI	2,08:1		209	2	5000-6000		-	12L		x	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F9.9 M EFI	S		x				x							EFI	2,08:1		209	2	5000-6000	40	-	12L		8M0215251	-	-	-	-	-	-	-	-	-	-	-	-	-	-
F9.9 ML EFI	L		x				x							EFI	2,08:1		209	2	5000-6000		-	12L	-		-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F9.9 EH EFI	S		x				x	x						EFI	2,08:1		209	2	5000-6000		-	12L	-		-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F9.9 ELH EFI	L		x				x	x						EFI	2,08:1		209	2	5000-6000		-	12L	-		-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F9.9 E EFI	S			x	x		x	x						EFI	2,08:1		209	2	5000-6000		-	12L	x		-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F9.9 EL EFI	L			x	x		x	x						EFI	2,08:1		209	2	5000-6000		-	12L	x		-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F9.9 MLH EFI CT	L		x				x							EFI	2,42:1	x	209	2	5000-6000		-	12L	-		-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F9.9 ELH EFI CT	L		x				x	x						EFI	2,42:1	x	209	2	5000-6000		-	12L	-		-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F9.9 EL EFI CT	L			x	x		x	x						EFI	2,42:1	x	209	2	5000-6000		-	12L	x		-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F9.9 ELPT EFI CT	L			x	x		x	x	x					EFI	2,42:1	x	209	2	5000-6000		-	12L	x		-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F10 M EFI	S		x				x							EFI	2,15:1		333	2	5700-6200	45	-	12L	13563Q3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax
F10 ML EFI	L		x				x							EFI	2,15:1		333	2	5700-6200		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F10 E EFI	S			x	x		x	x						EFI	2,15:1		333	2	5700-6200		-	12L		x	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F10 EL EFI	L			x	x		x	x						EFI	2,15:1		333	2	5700-6200		-	12L		x	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F15 M EFI	S		x				x							EFI	2,15:1		333	2	5700-6200	45	-	12L	13563Q3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax
F15 ML EFI	L		x				x							EFI	2,15:1		333	2	5700-6200		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F15 EH EFI	S		x				x	x						EFI	2,15:1		333	2	5700-6200		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F15 ELH EFI	L		x				x	x						EFI	2,15:1		333	2	5700-6200		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F15 E EFI	S			x	x		x	x						EFI	2,15:1		333	2	5700-6200		-	12L		x	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F15 EL EFI	L			x	x		x	x						EFI	2,15:1		333	2	5700-6200		-	12L		x	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F15 ELPT EFI	L			x	x		x	x	x					EFI	2,15:1		333	2	5700-6200		-	12L		x	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F20 M EFI	S		x				x							EFI	2,15:1		333	2	5700-6200	45	-	12L	13563Q3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax
F20 ML EFI	L		x				x							EFI	2,15:1		333	2	5700-6200		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F20 EH EFI	S		x				x	x						EFI	2,15:1		333	2	5700-6200		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F20 ELH EFI	L		x				x	x						EFI	2,15:1		333	2	5700-6200		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F20 ELHPT EFI	L						x	x	x					EFI	2,15:1		333	2	5700-6200		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F20 E EFI	S			x	x		x	x						EFI	2,15:1		333	2	5700-6200		-	12L		x	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F20 EL EFI	L			x	x		x	x						EFI	2,15:1		333	2	5700-6200		-	12L		x	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F20 EPT EFI	S			x	x		x	x	x					EFI	2,15:1		333	2	5700-6200		-	12L		x	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F20 ELPT EFI	L			x	x		x	x	x					EFI	2,15:1		333	2	5700-6200		-	12L		x	-	-	-	-	-	-	-	-	-	-	-	BlackMax		

Mercury Outboards - Specifications - Standard Accessories - 2025.1

Information on this sheet is subject to change without notice.

	Specifications																				Standard Accessories - Single Installation																			
	Shaft Length	Counter Rotation	Tiller Handle	Remote Control	Mechanical Throttle&Shift (MTS)	Digital Throttle&Shift (DTS)	Manual Start	Electric Start	Power Tilt	Power Trim	Conventional Mid Section (CMS)	Advanced Mid Section (AMS)	Optional "Cold Fusion White" Color	Fuel System	Gear Ratio	Command Thrust Gear Case (CT)	Displacement [ccm]	Cylinder	Max. RPM at Full Throttle	Dry Weight [kg] *	Integrated Fuel Tank	Remote Fuel Tank	Fuel Quick Connect on Engine Side	Side Remote Control	Tacho Analog	Speedo Analog	Trim Gauge Analog	SC1000 Tacho SmartCraft	SC1000 Speedo SmartCraft	SC100 Trim Gauge SamrtCraft	SC100 Fuel Gauge SamrtCraft	Electro-Hydraulic Steering	Active Trim	VesselView Mobile	SeaPro Fuel Filter	Propeller				
FourStroke																																								
F25 M EFI	S		x				x							EFI	2,17:1		500	3	5400-5800	60	-	25L	8M0215251	-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F25 ML EFI	L		x				x							EFI	2,17:1		500	3	5400-5800		-	25L		-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax			
F25 EH EFI	S		x					x						EFI	2,17:1		500	3	5400-5800		-	25L		-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax			
F25 ELH EFI	L		x					x						EFI	2,17:1		500	3	5400-5800		-	25L		-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax			
F25 ELHPT EFI	L		x					x						EFI	2,17:1		500	3	5400-5800		-	25L		-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax			
F25 E EFI	S			x	x			x						EFI	2,17:1		500	3	5400-5800		-	25L		-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F25 EL EFI	L			x	x			x						EFI	2,17:1		500	3	5400-5800		-	25L		-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F25 EPT EFI	S			x	x			x		x				EFI	2,17:1		500	3	5400-5800		-	25L		-	-	-	-	x	-	-	-	-	-	-	-	-	-	BlackMax		
F25 ELPT EFI	L			x	x			x		x				EFI	2,17:1		500	3	5400-5800		-	25L		-	-	-	-	x	-	-	-	-	-	-	-	-	-	BlackMax		
F30 M GA EFI	S		x					x						EFI	2,17:1		500	3	5800-6200	66	-	25L	8M0215251	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax	
F30 ML GA EFI	L		x				x							EFI	2,17:1		500	3	5800-6200		-	25L		-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F30 ELHPT EFI	L		x					x		x				EFI	2,17:1		500	3	5800-6200		-	25L		-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F30 EPT EFI	S			x	x			x		x				EFI	2,17:1		500	3	5800-6200		-	25L		-	-	-	-	x	-	-	-	-	-	-	-	-	-	BlackMax		
F30 ELPT EFI	L			x	x			x		x				EFI	2,17:1		500	3	5800-6200		-	25L		-	-	-	-	x	-	-	-	-	-	-	-	-	-	BlackMax		
F30 ELPT EFI CT	L			x	x			x		x				EFI	2,00:1	x	747	3	5800-6200		-	-		-	-	-	-	x	-	-	-	-	-	-	-	-	-	BlackMax		
F40 ELHPT EFI	L		x					x		x				EFI	2,00:1		747	3	5500-6000		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax		
F40 EPT EFI	S			x	x			x		x				EFI	2,00:1		747	3	5500-6000	98	-	-		-	-	-	-	x	x	x	x	-	-	-	-	-	-	-	BlackMax	
F40 ELPT EFI	L			x	x			x		x				EFI	2,00:1		747	3	5500-6000		-	-		-	-	-	-	x	x	x	x	-	-	-	-	-	-	-	BlackMax	
F40 ELPT EFI Orion	L			x	x			x		x				EFI	1,83:1		995	4	5500-6000	112	-	-	-	-	-	-	x	x	x	x	-	-	-	-	-	-	-	BlackMax		
F40 ELPT EFI CT Pro	L			x	x			x		x				EFI	2,33:1	x	995	4	5500-6000	118	-	-	-	-	-	-	x	x	x	x	-	-	-	-	-	-	-	BlackMax		
F50 ELHPT EFI	L		x					x		x				EFI	1,83:1		995	4	5500-6000		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax			
F50 ELPT EFI	L			x	x			x		x				EFI	1,83:1		995	4	5500-6000	112	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax			
F50 ELPT EFI CT	L			x	x			x		x				EFI	2,33:1	x	995	4	5500-6000	118	-	-	-	-	-	-	x	x	x	x	-	-	-	-	-	-	-	BlackMax		
F60 ELHPT EFI	L		x					x		x				EFI	1,83:1		995	4	5500-6000		-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax			
F60 ELPT EFI	L			x	x			x		x				EFI	1,83:1		995	4	5500-6000	112	-	-	-	-	-	-	x	x	x	x	-	-	-	-	-	-	-	BlackMax		
F60 ELPT EFI CT	L			x	x			x		x				EFI	2,33:1	x	995	4	5500-6000	118	-	-	-	-	-	-	x	x	x	x	-	-	-	-	-	-	-	BlackMax		
F80 ELPT EFI	L			x	x			x		x				EFI	2,07:1		2.064	4	4500-5500	163	-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	x	-	BlackMax
F100 L EFI	L			x	x			x		x				EFI	2,07:1		2.064	4	5000-6000	163	-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	x	-	BlackMax
F100 XL EFI	XL			x	x			x		x				EFI	2,07:1		2.064	4	5000-6000		-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	x	-	BlackMax
F100 L EFI CT	L			x	x			x		x				EFI	2,38:1	x	2.064	4	5000-6000	165	-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	x	-	BlackMax
F100 XL EFI CT	XL			x	x			x		x				EFI	2,38:1	x	2.064	4	5000-6000		-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	x	-	BlackMax
F115 L EFI	L			x	x			x		x				EFI	2,07:1		2.064	4	5000-6000	163	-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	x	-	BlackMax
F115 XL EFI	XL			x	x			x		x				EFI	2,07:1		2.064	4	5000-6000		-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	x	-	BlackMax
F115 L EFI CT	L			x	x			x		x				EFI	2,38:1	x	2.064	4	5000-6000		-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	x	-	BlackMax
F115 XL EFI CT	XL			x	x			x		x				EFI	2,38:1	x	2.064	4	5000-6000	165	-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	x	-	BlackMax
F115 CXL EFI CT	XL	x		x	x			x		x				EFI	2,38:1	x	2.064	4	5000-6000		-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	-	-	BlackMax
F150 L EFI	L			x	x			x		x			x	EFI	1,92:1		3.000	4	5000-5800	206	-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	x	-	Revolution4
F150 XL EFI	XL			x	x			x		x			x	EFI	1,92:1		3.000	4	5000-5800		-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	x	-	Revolution4
F150 CXL EFI	XL	x		x	x			x		x			x	EFI	1,92:1		3.000	4	5000-5800		-	-	-	-	-	-	x	-	-	-	-	x	x	x	-	-	-	-	-	Revolution4
F175 L	L			x		x		x		x	x			EFI	1,85:1		3.400	V6	5000-5800	216	-	-	-	-	-	-	x	-	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F175 XL	XL			x		x		x		x	x			EFI	1,85:1		3.400	V6	5000-5800		-	-	-	-	-	-	x	-	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F175 CXL	XL	x		x		x		x		x	x			EFI	1,85:1		3.400	V6	5000-5800		-	-	-	-	-	-	x	-	-	-	-	x	x	x	x	-	-	-	-	Revolution4
F200 L	L			x		x		x		x	x		x	EFI	1,85:1		3.400	V6	5000-5800	216	-	-	-	-	-	-	x	-	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F200 XL	XL			x		x		x		x	x		x	EFI	1,85:1		3.400	V6	5000-5800		-	-	-	-	-	-	x	-	-	-	-	x	x	x	x	-	x	x	-	Revolution4
F200 CXL	XL	x		x		x		x		x	x		x	EFI	1,85:1		3.400	V6	5000-5800		-	-	-	-	-	-	x	-	-	-	-	x	x	x	x	-	-	-	-	Revolution4

Mercury Outboards - Specifications - Standard Accessories - 2025.1

Information on this sheet is subject to change without notice.

	Specifications																				Standard Accessories - Single Installation																	
	Shaft Length	Counter Rotation	Tiller Handle	Remote Control	Mechanical Throttle&Shift (MTS)	Digital Throttle&Shift (DTS)	Manual Start	Electric Start	Power Tilt	Power Trim	Conventional Mid Section (CMS)	Advanced Mid Section (AMS)	Optional "Cold Fusion White" Color	Fuel System	Gear Ratio	Command Thrust Gear Case (CT)	Displacement [ccm]	Cylinder	Max. RPM at Full Throttle	Dry Weight [kg] *	Integrated Fuel Tank	Remote Fuel Tank	Fuel Quick Connect on Engine Side	Side Remote Control	Tacho Analog	Speedo Analog	Trim Gauge Analog	SC1000 Tacho SmartCraft	SC1000 Speedo SmartCraft	SC100 Trim Gauge SamrtCraft	SC100 Fuel Gauge SamrtCraft	Electro-Hydraulic Steering	Active Trim	VesselView Mobile	SeaPro Fuel Filter	Propeller		
FourStroke																																						
F225 L	L			x		x		x		x	x		x	EFI	1,85:1		3.400	V6	5200-6000	216	-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F225 XL	XL			x		x		x		x	x		x	EFI	1,85:1		3.400	V6	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F225 CXL	XL	x		x		x		x		x	x		x	EFI	1,85:1		3.400	V6	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	-	-	-	Revolution4		
F225 XXL	XXL			x		x		x		x	x		x	EFI	1,85:1		3.400	V6	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F225 CXXL	XXL	x		x		x		x		x	x		x	EFI	1,85:1		3.400	V6	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	-	-	-	Revolution4		
F250 XL	XL			x		x		x		x	x			EFI	1,75:1		4.600	V8	5200-6000	239	-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F225 CXL	XL	x		x		x		x		x	x			EFI	1,75:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	-	-	-	Revolution4		
F300 XL	XL			x		x		x		x	x			EFI	1,75:1		4.600	V8	5200-6000	239	-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F300 CXL	XL	x		x		x		x		x	x			EFI	1,75:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	-	-	-	-	Revolution4		
Verado																																						
F250 L Verado	L			x		x		x		x		x	x	EFI	1,85:1		4.600	V8	5200-6000	272	-	-	-	x	-	-	-	x	x	x	x	x	x	x	-	Revolution4		
F250 XL Verado	XL			x		x		x		x		x	x	EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	x	x	-	Revolution4		
F250 CXL Verado	XL	x		x		x		x		x		x	x	EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	Revolution4		
F250 XXL Verado	XXL			x		x		x		x		x	x	EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	Revolution4		
F250 CXXL Verado	XXL	x		x		x		x		x		x	x	EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	Revolution4		
F300 L Verado	L			x		x		x		x		x	x	EFI	1,85:1		4.600	V8	5200-6000	272	-	-	-	x	-	-	-	x	x	x	x	x	x	x	-	Revolution4		
F300 CL Verado	L	x		x		x		x		x		x	x	EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	Revolution4		
F300 XL Verado	XL			x		x		x		x		x	x	EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	Revolution4		
F300 CXL Verado	XL	x		x		x		x		x		x	x	EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	Revolution4		
F300 XXL Verado	XXL			x		x		x		x		x	x	EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	Revolution4		
F300 CXXL Verado	XXL	x		x		x		x		x		x	x	EFI	1,85:1		4.600	V8	5200-6000		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	Revolution4		
F350 L Verado	L			x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400	316	-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	RevolutionX		
F350 CL Verado	L	x		x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	RevolutionX		
F350 XL Verado	XL			x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	RevolutionX		
F350 CXL Verado	XL	x		x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	RevolutionX		
F350 XXL Verado	XXL			x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	RevolutionX		
F350 CXXL Verado	XXL	x		x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	RevolutionX		
F350 XXXL Verado	XXXL			x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	RevolutionX		
F350 CXXXL Verado	XXXL	x		x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	RevolutionX		
F400 L Verado	L			x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400	316	-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	RevolutionX		
F400 CL Verado	L	x		x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	RevolutionX		
F400 XL Verado	XL			x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	RevolutionX		
F400 CXL Verado	XL	x		x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	RevolutionX		
F400 XXL Verado	XXL			x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	RevolutionX		
F400 CXXL Verado	XXL	x		x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	RevolutionX		
F400 XXXL Verado	XXXL			x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	RevolutionX		
F400 CXXXL Verado	XXXL	x		x		x		x		x		x	x	EFI	2,08:1		5.700	V10	5800-6400		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	RevolutionX		
F600 L Verado	L	x		x		x		x		x		x	x	EFI	2,50:1		7.600	V12	5600-6400	572	-	-	-	x	-	-	-	VV 903 included				x	x	x	-	Verado12		
F600 XL Verado	XL	x		x		x		x		x		x	x	EFI	2,50:1		7.600	V12	5600-6400		-	-	-	x	-	-	-	VV 903 included				x	x	x	-	Verado12		
F600 XXL Verado	XXL	x		x		x		x		x		x	x	EFI	2,50:1		7.600	V12	5600-6400		-	-	-	x	-	-	-	VV 903 included				x	x	x	-	Verado12		
F600 XXXL Verado	XXXL	x		x		x		x		x		x	x	EFI	2,50:1		7.600	V12	5600-6400		-	-	-	x	-	-	-	VV 903 included				x	x	x	-	Verado12		

Mercury Outboards - Specifications - Standard Accessories - 2025.1

Information on this sheet is subject to change without notice.

	Specifications																			Standard Accessories - Single Installation																		
	Shaft Length	Counter Rotation	Tiller Handle	Remote Control	Mechanical Throttle&Shift (MTS)	Digital Throttle&Shift (DTS)	Manual Start	Electric Start	Power Tilt	Power Trim	Conventional Mid Section (CMS)	Advanced Mid Section (AMS)	Optional "Cold Fusion White" Color	Fuel System	Gear Ratio	Command Thrust Gear Case (CT)	Displacement [ccm]	Cylinder	Max. RPM at Full Throttle	Dry Weight [kg] *	Integrated Fuel Tank	Remote Fuel Tank	Fuel Quick Connect on Engine Side	Side Remote Control	Tacho Analog	Speedo Analog	Trim Gauge Analog	SC1000 Tacho SmartCraft	SC1000 Speedo SmartCraft	SC100 Trim Gauge SamrtCraft	SC100 Fuel Gauge SamrtCraft	Electro-Hydraulic Steering	Active Trim	VesselView Mobile	SeaPro Fuel Filter	Propeller		
Pro XS																																						
F115 L Pro XS	L			x	x			x		x				EFI	2,07:1		2.064	4	5300-600	163	-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	BlackMax		
F115 XL Pro XS	XL			x	x			x		x				EFI	2,07:1		2.064	4	5300-6300		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	BlackMax		
F115 L Pro XS CT	L			x	x			x		x				EFI	2,38:1	x	2.064	4	5300-6300	165	-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	BlackMax		
F115 XL Pro XS CT	XL			x	x			x		x				EFI	2,38:1	x	2.064	4	5300-6300		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	BlackMax		
F150 L Pro XS	L			x	x			x		x				EFI	2,08:1		3.000	4	5200-6000	207	-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4		
F150 XL Pro XS	XL			x	x			x		x				EFI	2,08:1		3.000	4	5200-6000		-	-	-	x	-	-	-	x	x	x	-	-	-	x	-	Revolution4		
F175 L Pro XS MTS	L			x	x			x		x	x			EFI	1,85:1		3.400	V6	5400-6000	213	-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F175 XL Pro XS MTS	XL			x	x			x		x	x			EFI	1,85:1		3.400	V6	5400-6000		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F200 XL Pro XS	XL			x		x		x		x	x			EFI	1,85:1		4.600	V8	5600-6200	229	-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F200 L Pro XS TM DTS	L			x		x		x		x	x			EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F200 L Pro XS TM MTS	L			x	x			x		x	x			EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F225 XL Pro XS	XL			x		x		x		x	x			EFI	1,75:1		4.600	V8	5600-6200	229	-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F225 L Pro XS TM DTS	L			x		x		x		x	x			EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F250 XL Pro XS	XL			x		x		x		x	x			EFI	1,75:1		4.600	V8	5600-6200	229	-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F250 CXL Pro XS	XL	x		x		x		x		x	x			EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	x	-	-	-	-	Revolution4		
F250 L Pro XS TM DTS	L			x		x		x		x	x			EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F300 XL Pro XS	XL			x		x		x		x	x			EFI	1,75:1		4.600	V8	5600-6200	229	-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		
F300 CXL Pro XS	XL	x		x		x		x		x	x			EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	x	-	-	-	-	Revolution4		
F300 L Pro XS TM DTS	L			x		x		x		x	x			EFI	1,75:1		4.600	V8	5600-6200		-	-	-	x	-	-	-	x	x	x	x	-	x	x	-	Revolution4		

* Dry weight is for the lightest model and excludes engine oil, rigging, and propeller.

Dual Installations of FourStroke engines 115 HP up to 150 HP include the following instruments: 2x SC1000 Tacho, 1x SC1000 Speedo, 2x SC100 Trim Gauge, 1x VesselView Mobile

Dual Installations of FourStroke, Verado and Pro XS engines 175 HP up to 400 HP include the following instruments: 2x SC1000 Tacho, 1x SC1000 Speedo, 2x SC100 Trim Gauge, 1x SC100 Fuel Gauge, 1x VesselView Mobile

Mercury Outboards - Specifications - Standard Accessories - 2025.1

Information on this sheet is subject to change without notice.

	Specifications																				Standard Accessories - Single Installation																										
	Shaft Length	Counter Rotation	Tiller Handle	Remote Control	Mechanical Throttle&Shift (MTS)	Digital Throttle&Shift (DTS)	Manual Start	Electric Start	Power Tilt	Power Trim	Conventional Mid Section (CMS)	Advanced Mid Section (AMS)	Optional "Cold Fusion White" Color	Fuel System	Gear Ratio	Command Thrust Gear Case (CT)	Displacement [ccm]	Cylinder	Max. RPM at Full Throttle	Dry Weight [kg] *	Integrated Fuel Tank	Remote Fuel Tank	Fuel Quick Connect on Engine Side	Side Remote Control	Tacho Analog	Speedo Analog	Trim Gauge Analog	SC1000 Tacho SmartCraft	SC1000 Speedo SmartCraft	SC100 Trim Gauge SamrtCraft	SC100 Fuel Gauge SamrtCraft	Electro-Hydraulic Steering	Active Trim	VesselView Mobile	SeaPro Fuel Filter	Propeller											
SeaPro																																															
F15 M SeaPro	S		x				x							EFI	2,15:1		333	2	5700-6200	45	-	12L	13569Q3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax Alu									
F15 ML SeaPro	L		x				x							EFI	2,15:1		333	2	5700-6200		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax Alu										
F15 EL SeaPro	L			x	x			x	x					EFI	2,15:1		333	2	5700-6200		-	12L		-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax Alu									
F25 M SeaPro	S		x				x							EFI	2,17:1		500	3	5400-5800	60	-	25L	8M0215251	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax Alu								
F25 ML SeaPro	L		x					x						EFI	2,17:1		500	3	5400-5800		-	25L		-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax Alu									
F25 EL SeaPro	L			x	x			x						EFI	2,17:1		500	3	5400-5800		-	25L		-	-	-	-	-	-	-	-	-	-	-	-	-	-	BlackMax Alu									
F40 ELPT SeaPro	L			x	x			x		x				EFI	2,33:1	x	995	4	4500-5500		-	-	13569Q3	x	-	-	-	-	x	-	-	-	-	-	-	-	-	x	BlackMax Alu								
F40 EXLPT SeaPro	XL			x	x			x	x					EFI	2,33:1	x	995	4	4500-5500		-	-		x	-	-	-	-	x	-	-	-	-	-	-	-	x	BlackMax Alu									
F40 ELHPT SeaPro	L		x					x	x					EFI	2,33:1	x	995	4	4500-5500		-	-		-	-	-	-	-	x	-	-	-	-	-	-	-	x	BlackMax Alu									
F60 ELPT SeaPro	L			x	x			x	x					EFI	2,33:1	x	995	4	5000-5500		-	-	13569Q3	x	-	-	-	-	x	-	-	-	-	-	-	-	-	x	BlackMax Alu								
F60 EXLPT SeaPro	XL			x	x			x	x					EFI	2,33:1	x	995	4	5000-5500		-	-		x	-	-	-	-	x	-	-	-	-	-	-	-	x	BlackMax Alu									
F60 ELHPT SeaPro	L		x					x	x					EFI	2,33:1	x	995	4	5000-5500		-	-		-	-	-	-	-	x	-	-	-	-	-	-	-	x	BlackMax Alu									
F60 EXLHPT SeaPro	XL		x					x	x					EFI	2,33:1	x	995	4	5000-5500		-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	x	BlackMax Alu									
F75 ELPT SeaPro	L			x				x	x					EFI	2,38:1	x	2.064	4	5000-5500	165	-	-	-	x	-	-	-	-	x	-	x	x	-	-	-	x	x	Revolution4									
F75 ELHPT SeaPro	L		x					x	x					EFI	2,38:1	x	2.064	4	5000-5500		-	-	-	-	-	-	-	x	-	x	x	-	-	-	-	x	x	Revolution4									
F90 ELPT SeaPro	L			x	x			x	x					EFI	2,38:1	x	2.064	4	5000-5500	165	-	-	-	x	-	-	-	-	x	-	x	x	-	-	-	-	x	x	Revolution4								
F90 EXLPT SeaPro	XL			x	x			x	x					EFI	2,38:1	x	2.064	4	5000-5500		-	-	-	x	-	-	-	-	x	-	x	x	-	-	-	-	x	x	Revolution4								
F90 ELHPT SeaPro	L		x					x	x					EFI	2,38:1	x	2.064	4	5000-5500		-	-	-	-	-	-	-	-	x	-	x	x	-	-	-	-	x	x	Revolution4								
F90 EXLHPT SeaPro	XL		x					x	x					EFI	2,38:1	x	2.064	4	5000-5500		-	-	-	-	-	-	-	-	x	-	x	x	-	-	-	-	x	x	Revolution4								
F115 ELPT SeaPro	L			x	x			x	x					EFI	2,38:1	x	2.064	4	5000-5500	165	-	-	-	x	-	-	-	-	x	-	x	x	-	-	-	-	x	x	Revolution4								
F115 EXLPT SeaPro	XL			x	x			x	x					EFI	2,38:1	x	2.064	4	5000-5500		-	-	-	x	-	-	-	-	x	-	x	x	-	-	-	-	x	x	Revolution4								
F115 ECXLPT SeaPro	XL	x		x	x			x	x					EFI	2,38:1	x	2.064	4	5000-5500		-	-	-	x	-	-	-	-	x	-	x	x	-	-	-	-	-	x	Revolution4								
F115 ELHPT SeaPro	XL		x					x	x					EFI	2,38:1	x	2.064	4	5000-5500		-	-	-	-	-	-	-	-	x	-	x	x	-	-	-	-	-	x	Revolution4								
F150 L SeaPro	L			x	x			x	x					EFI	2,08:1		3.000	4	4800-5300	206	-	-	-	x	-	-	-	-	x	-	x	x	-	-	-	-	x	x	Revolution4								
F150 XL SeaPro	XL			x	x			x	x					EFI	2,08:1		3.000	4	4800-5300		-	-	-	-	-	-	-	-	x	-	x	x	-	-	-	-	-	x	Revolution4								
F150 CXL SeaPro	XL	x		x	x			x	x					EFI	2,08:1		3.000	4	4800-5300		-	-	-	-	-	-	-	-	x	-	x	x	-	-	-	-	-	-	x	Revolution4							
F200 XL SeaPro	XL			x		x		x		x	x			EFI	1,85:1		3.400	V6	4600-5400		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	x	Revolution4							
F200 CXL SeaPro	XL	x		x		x		x	x	x				EFI	1,85:1		3.400	V6	4600-5400		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	x	Revolution4							
F225 L SeaPro	L			x	x			x	x	x				EFI	1,75:1		4.600	V8	4800-5600	239	-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	x	Revolution4							
F225 CL SeaPro	L	x		x	x	x		x	x	x				EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	x	Revolution4							
F225 XL SeaPro	XL			x	x			x	x	x				EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	x	Revolution4						
F225 CXL SeaPro	XL	x		x		x		x	x	x	x			EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	x	Revolution4						
F225 XXL SeaPro	XXL			x	x			x	x	x	x			EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	x	Revolution4						
F225 CXXL SeaPro	XXL	x		x		x		x	x	x	x			EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4					
F250 XL SeaPro	XL			x		x		x	x	x				EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4					
F250 CXL SeaPro	XL	x		x		x		x	x	x				EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4					
F250 XXL SeaPro	XXL			x		x		x	x	x				EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4				
F250 CXXL SeaPro	XXL	x		x		x		x	x	x	x			EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4				
F300 XL SeaPro	XL			x		x		x	x	x				EFI	1,75:1		4.600	V8	4800-5600	239	-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4				
F300 CXL SeaPro	XL	x		x		x		x	x	x				EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4			
F300 XXL SeaPro	XXL			x		x		x	x	x				EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4			
F300 CXXL SeaPro	XXL	x		x		x		x	x	x	x			EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4		
F300 XL SeaPro - AMS	XL			x		x		x	x			x		EFI	1,75:1		4.600	V8	4800-5600	272	-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4		
F300 CXL SeaPro - AMS	XL	x		x		x		x	x			x		EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4	
F300 XXL SeaPro - AMS	XXL			x		x		x	x			x		EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	x	Revolution4
F300 CXXL SeaPro - AMS	XXL	x		x		x		x	x			x		EFI	1,75:1		4.600	V8	4800-5600		-	-	-	-	-	-	-	-	x	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	

Mercury Outboards - Specifications - Standard Accessories - 2025.1

Information on this sheet is subject to change without notice.

	Specifications																				Standard Accessories - Single Installation																	
	Shaft Length	Counter Rotation	Tiller Handle	Remote Control	Mechanical Throttle&Shift (MTS)	Digital Throttle&Shift (DTS)	Manual Start	Electric Start	Power Tilt	Power Trim	Conventional Mid Section (CMS)	Advanced Mid Section (AMS)	Optional "Cold Fusion White" Color	Fuel System	Gear Ratio	Command Thrust Gear Case (CT)	Displacement [ccm]	Cylinder	Max. RPM at Full Throttle	Dry Weight [kg] *	Integrated Fuel Tank	Remote Fuel Tank	Fuel Quick Connect on Engine Side	Side Remote Control	Tacho Analog	Speedo Analog	Trim Gauge Analog	SC1000 Tacho SmartCraft	SC1000 Speedo SmartCraft	SC100 Trim Gauge SamrtCraft	SC100 Fuel Gauge SamrtCraft	Electro-Hydraulic Steering	Active Trim	VesselView Mobile	SeaPro Fuel Filter	Propeller		
SeaPro																																						
F350 XL SeaPro	XL			x		x		x		x		x		EFI	2,08:1		5.700	V10	5300-5900	316	-	-	-	x	-	-	-	x	x	x	x	x	x	x	x	-	RevolutionX	
F350 CXL SeaPro	XL	x		x		x		x		x		x		EFI	2,08:1		5.700	V10	5300-5900		-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	-	RevolutionX	
F350 XXL SeaPro	XXL			x		x		x		x		x		EFI	2,08:1		5.700	V10	5300-5900		-	-	-	x	-	-	-	x	x	x	x	x	x	x	-	-	RevolutionX	
F350 CXXL SeaPro	XXL	x		x		x		x		x		x		EFI	2,08:1		5.700	V10	5300-5900		-	-	-	x	-	-	-	x	x	x	x	x	x	-	-	-	RevolutionX	
F350 XXXL SeaPro	XXXL			x		x		x		x		x		EFI	2,08:1		5.700	V10	5300-5900		-	-	-	x	-	-	-	x	x	x	x	x	x	x	-	-	RevolutionX	
F350 CXXXL SeaPro	XXXL	x		x		x		x		x		x		EFI	2,08:1		5.700	V10	5300-5900		-	-	-	x	-	-	-	x	x	x	x	x	-	-	-	RevolutionX		
F500 L SeaPro	L	x			x	x		x		x		x		EFI	2,50:1		7.600	V12	5000-5800	572	-	-	-	x	-	-	-	VV 903 included				x	x	x	-	Verado12		
F500 XL SeaPro	XL	x		x		x		x		x		x		EFI	2,50:1		7.600	V12	5000-5800		-	-	-	x	-	-	-	VV 903 included				x	x	x	-	Verado12		
F500 XXL SeaPro	XXL	x		x		x		x		x		x		EFI	2,50:1		7.600	V12	5000-5800		-	-	-	x	-	-	-	VV 903 included				x	x	x	-	Verado12		
F500 XXXL SeaPro	XXXL	x		x		x		x		x		x		EFI	2,50:1		7.600	V12	5000-5800		-	-	-	x	-	-	-	VV 903 included				x	x	x	-	Verado12		

* Dry weight is for the lightest model and excludes engine oil, rigging, and propeller.

** SeaPro Engines are shipped with SmartCraft Instruments with black face

Dual Installations of SeaPro engines 115 HP up to 300 HP include the following instruments: 2x SC1000 Tacho, 2x SC100 Trim Gauge, 1x SC100 Fuel Gauge, 1x VesselView Mobile